


# Steel Wire Rope Forest King

## Інформація про товар



sZ T C

The most important advantage of ropes with such a construction is the excellent abrasion resistance of the outer surface of the rope and the significantly increased breaking strength of the rope, compared to a rope of standard design with the same diameter. FOREST KING rope is proven ideal in the forest industry for skidding and timber transportation.

**Маркування:** Згідно зі стандартом

**Стандарт:** EN 12385-4

**Коефіцієнт заповнення:** 0,657

**RCN:** 06

**Відхилення Ø:** 0% to +5%

Код товару	Діаметр троса мм	Tensile strength N/mm <sup>2</sup>	Покриття	Rope lay	Мінімальна розривна сила кН 2160Н\мм <sup>2</sup>	Площа перерізу мм <sup>2</sup>	Мастило	Вага кг/м
103101004090990	10	2 060	Неоцинковане	sZ	104	-	Dry	0,57
103101104090990	11	2 060	Неоцинковане	sZ	123	-	Dry	0,7
103101204090990	12	2 060	Неоцинковане	sZ	144	-	Dry	0,83
103101304090990	13	2 060	Неоцинковане	sZ	165	-	Dry	0,98
103101404090990	14	2 060	Неоцинковане	sZ	188	-	Dry	1,15