# Heavy Duty Air Chain Hoists Red Rooster TMH (25.000 & 30.000 kg)

**Інформація про товар**



The Red Rooster TMH series air chain hoists have the highest lifting speed with the lowest headroom on the hoist market. With classification of mechanism, M3 for the TMH-25 and M2 for the TMH-30, these hoists are extremely reliable. This hoist will guarantee the continuity of your process.

**Standard features:**

- Precise variable speed control (cord control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Low noise level (84 dBA)
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

**ATEX:**

- According to EC Directive 94/9/EC (Ex Classification)

**Recommended:** We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

... *Read more*

**Маркування:** Згідно зі стандартом, CE-marked
**Стандарт:** EN 14492-2


**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Heavy Duty Air Chain Hoists Red Rooster TMH (25.000 & 30.000 kg)

## Креслення



## Technical data

| Код товару | Вантажопідйомність тон | Тип | Chain falls | Швидкість підйому м\хв | Air consumption lowering (l/sec) | Air consumption lifting l/sec | Швидкість підйому м\хв | Lowering speed with max.load m/min | A мм | B мм | C мм | D мм | E мм | F мм | G мм | H мм | I мм | J мм | K мм | L мм | M мм | N мм | O мм | P мм | Q мм | R мм | Bara кг |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 5601TMH25TC2 | 25 | Cord control | 2 | 2,7 | 180 | 108 | 1,4 | 3 | 1 290 | 566 | 223 | 343 | 330 | 82 | 285 | 708 | 352 | 356 | 90 | ø100 | 71 | 732 | 558 | 71 | 100 | 90 | 581 |
| 5601TMH25TP2E | 25 | Pendant control | 2 | 2,7 | 180 | 108 | 1,4 | 3 | 1 290 | 566 | 223 | 343 | 330 | 82 | 285 | 708 | 352 | 356 | 90 | ø100 | 71 | 732 | 558 | 71 | 100 | 90 | 581 |
| 5601TMH30TC2 | 30 | Cord control | 2 | 2,7 | 167 | 108 | 1 | 2,7 | 1 290 | 566 | 223 | 343 | 330 | 82 | 285 | 708 | 352 | 356 | 90 | ø100 | 71 | 732 | 558 | 71 | 100 | 90 | 581 |
| 5601TMH30TP2E | 30 | Pendant control | 2 | 2,7 | 167 | 108 | 1 | 2,7 | 1 290 | 566 | 223 | 343 | 330 | 82 | 285 | 708 | 352 | 356 | 90 | ø100 | 71 | 732 | 558 | 71 | 100 | 90 | 581 |

**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved