

## Lifting Magnet REVOLIFT Permanent

### Інформація про товар



The Revolift product is an innovative lifting magnet from Walmag that offers several unique features that make it ideal for a variety of steel handling situations and applications. It is ideal for steel handling professionals, including situations where you need to lift or handle steel materials of various shapes, sizes and quality. Safety, reliability and innovation go hand in hand with Revolift to make your job easier and improve your productivity.

It easily handles flat, round, and cylindrical loads with emphasis on safety and convenience. Each magnet is tested for break-away force with an air gap to simulate real operating conditions. The magnet body is highly resistant to mechanical damage, the bearings are secured, so their life span is longer. The magnet features a versatile lifting eye design for easy suspension. The magnet enables load handling at a maximum temperature of 80°C.

**Load test feature:** An unique technical solution of a test position which you can use whenever you are unsure if you can make a fully safe lift in case of irregular material, airgap, thin wall, bigger dimensions, unknown material quality, etc. The Load test option is always available to show you if your Revolift magnet has sufficient lifting capacity.

#### Features:

- Robust lifting eye made of stainless steel.
- 5-year warranty for the magnetic system.
- The magnet meets the 3+ safety factor - verified by the tear-off test.
- Load test feature
- Top handle position
- Better ergonomoy
- Simple safety tags
- Integrated NFC chip
- Online manual
- Scratch resistant tags

**Маркування:** Згідно зі стандартом, CE-marked

**Стандарт:** EN 13155

**Коефіцієнт запасу міцності:** 3:1

Код товару	Код	Вантажопідйомність тон	Eye diameter mm	WLL round materials t	H mm	L	W mm	Вага кг
503100020000480	REVO150	0,15	10	0,065	123	97	60	3,1
503100030000480	REVO300	0,3	16	0,15	180	152	100	10,4
503100060000480	REVO600	0,6	20	0,3	184	246	120	20,6
503100100000480	REVO1000	1	20	0,5	241	305,5	146	40
503100200000480	REVO2000	2	20	1	285	492	165	98,7

## Креслення

