Lifting Solutions Group
Axel Johnson International

Weld-On Hook Powertex WH

Інформація про товар



The Powertex WH weld-on hook is a permanent load connection point for welding onto lifting beams, excavators and other earth-moving machinery. It is designed for loading within a 135° area in the intended load plane, from +45° to -90° relative to the weld-on surface.

Best used for

- Permanent hook attachment on lifting beams and earth-moving machinery.

Product benefits

- 135° permitted loading area provides flexibility within the intended load plane.
- Unpainted weld base enables immediate welding with reduced smoke and fumes.
- Powder-coated hook provides corrosion and wear resistance.
- Tested in accordance with EN 1677-1 and AS 3776 requirements.
- Each hook is crack-detection tested, and production samples are proof-load tested. The product design is fatigue-tested to 20,000 cycles at 1.5 times the WLL.
- The traceability code links components to the production lot and raw materials.
- Full WLL from -40°C to +200°C, with reductions at higher temperatures

... *Read more*

Маркування: CE-marked, UKCA-marked


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Weld-On Hook Powertex WH

Креслення



Technical data

Код товару	Код	Вантажопідйомність тон	A мм	B мм	C мм	E мм	F мм	H мм	M мм	L мм	P мм	Вага кг
420500101250	WH-1T	1	23	76	63	22	18	93	22,5	101	25	0,54
420500201250	WH-2T	2	29	92	66	26	20,5	81	23,3	111	34	0,87
420500301250	WH-3T	3	30	106	75	30	24	116	30	128	36	1,3
420500501250	WH-5T	5	39	133	98	36	28	160	43	176	43,5	2,7
420500801250	WH-8T	8	36	137	99	34,5	39	166	50	175	51	3,5
420501001250	WH-10T	10	49	169	140	49	38	205	55	222	53	5,2

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved