

Weld-On Lashing Load Ring RUD LRBS-FIX

Інформація про товар



LRBS-FIX Lashing-Load ring for welding with circumferential weld seam.


- Bracket can be pivoted through 180°.
- LC possible up to 90° in load ring plane.
- Clear indication of the lashing capacity in daN.
- With all-round welding seam.
- Thanks to the weld arrangement (circular fillet weld), no contact/crevice corrosion can occur.
- For use on loading areas and loads.
- Split force introduction thanks to multiple point fixing.
- The clamping spring achieves noise reduction and keeps the suspension ring in the desired direction.

... [Read more](#)

Маркування: Згідно зі стандартом
Стандарт: EN 1677

Weld-On Lashing Load Ring RUD LRBS-FIX

Креслення



Technical data

Код товару	Код	Максимально допустиме робоче навантаження daN	T мм	A мм	B мм	C мм	D мм	E мм	F мм	Вага кг
70987999303	LRBS-FIX 8000 daN	8 000	74	60	14	39	48	132	69	0,94
70987913750	LRBS-FIX 13400 daN	13 400	97	88	20	50	60	167	91	2,24
70987999305	LRBS-FIX 20000 daN	20 000	108	100	22	60	65	191	100	3,72
70987999306	LRBS-FIX 32000 daN	32 000	140	130	30	72	90	267	134	8,23