# Manhole Clamp

**Інформація про товар**



The manhole clamp is used for the transport and laying of manholes. No adjustment of the clamping range is necessary. Accidents caused by incorrect adjustment are excluded. Due to the holdfast application the clamp must not be lifted when applying and disconnecting.

**Features:**

- Simple applying and disconnecting by means of holdfast application: clamp must not be lifted manually
- No adjustment of the clamping range
- Huge multiplication guarantees optimum safety
- Manhole clamp SZA for manholes and cones according to DIN 4034 Part 1 and 2
- With spring tension
- With web sling or high-strength chains

... *Read more*

**Коефіцієнт запасу міцності:** 5:1

**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Manhole Clamp

## Technical data

| Код товару | Код | Вантажопідйомність<br>тон | Jaw width<br>мм | Вага<br>кг |
|---|---|---|---|---|
| 502100101203010 | SZM 1 | 1 | 40-120 | 16 |
| 502100151203010 | SZM 1.5 | 1,5 | 40-120 | 28 |
| 502100151203014 | SZML 1.5 | 1,5 | 40-120 | 29 |
| 502100151203015 | SZM 1.5 K | 1,5 | 40-120 | 32 |
| 502100201803010 | SZA 2 | 2 | 60-180 | 28 |
| 502100201803014 | SZA 2K | 2 | 60-180 | 31 |
| 502100301803010 | SZA 3 | 3 | 60-180 | 40 |
| 502100301803014 | SZAL 3 | 3 | 60-180 | 41 |
| 502100301803015 | SZA 3 K | 3 | 60-180 | 45 |
| 502100301803016 | SZAL 3 K | 3 | 60-180 | 47 |
| 502100401803010 | SZA 4 | 4 | 60-180 | 55 |

**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved