

Chain Sling Powertex 4-leg with Masterlink MC4 and Safety Hooks, Grade 10

Інформація про товар



The Chain Sling Powertex 4-leg MC-4 with safety hooks is a four-leg lifting assembly for general industrial use. It features an MC-4 master link with integrated shortening functions on all 4 legs, reducing the number of components and creating a more compact and manageable lifting setup.

It is designed for balanced lifting where load distribution, individual leg adjustment, and predictable performance are required.

The assembly includes the MC-4 Master Link, Grade 10 chain, safety hooks, and a marking plate with WLL information, providing a complete, ready-to-use configuration.

Best used for:

- Lifting loads requiring multiple lifting points for stability
- Applications where a compact setup with integrated shortening is preferred
- Lifting applications where secure hook closure is required to reduce the risk of unintentional release

Product Benefits

- MC-4 master link integrates the shortening function, reducing the number of components and simplifying assembly configuration
- Individual leg shortening allows accurate load balancing without adding separate shortening hooks
- Compact design supports a clearer overview during use and inspection, helping reduce handling errors
- Safety hooks provide secure closure, helping reduce the chance of unintentional hook release during lifting
- Grade 10 chain provides higher capacity compared to Grade 8, enabling compact setups without increasing chain diameter

[... Read more](#)

Маркування: Згідно зі стандартом, CE-marked

Стандарт: EN 818-4, AS 3776

(+25 % WLL)

Коефіцієнт запасу міцності: 4:1

Клас: 10

Chain Sling Powertex 4-leg with Masterlink MC4 and Safety Hooks, Grade 10

Technical data

Код товару	Діаметр ланцюга мм	Вантажопідйомність тон	Ефективна робоча довжина m	WLL 0-45° t	WLL 45-60° t
241300600100310	6	3	1	3	2,12
241300600200310	6	3	2	3	2,12
241300600300310	6	3	3	3	2,12
241300600400310	6	3	4	3	2,12
241300600500310	6	3	5	3	2,12
241300600600310	6	3	6	3	2,12
241300600700310	6	3	7	3	2,12
241300600800310	6	3	8	3	2,12
241300800100310	8	5,3	1	5,3	3,75
241300800200310	8	5,3	2	5,3	3,75
241300800300310	8	5,3	3	5,3	3,75
241300800400310	8	5,3	4	5,3	3,75
241300800500310	8	5,3	5	5,3	3,75
241300800600310	8	5,3	6	5,3	3,75
241300800700310	8	5,3	7	5,3	3,75
241300800800310	8	5,3	8	5,3	3,75
241301000100310	10	8,4	1	8,4	6
241301000200310	10	8,4	2	8,4	6
241301000300310	10	8,4	3	8,4	6
241301000400310	10	8,4	4	8,4	6
241301000500310	10	8,4	5	8,4	6
241301000600310	10	8,4	6	8,4	6
241301000700310	10	8,4	7	8,4	6
241301000800310	10	8,4	8	8,4	6
241301300200310	13	14	2	14	10
241301300300310	13	14	3	14	10
241301300400310	13	14	4	14	10
241301300500310	13	14	5	14	10
241301300600310	13	14	6	14	10
241301300700310	13	14	7	14	10

Chain Sling Powertex 4-leg with Masterlink MC4 and Safety Hooks, Grade 10

Technical data

Код товару	Діаметр ланцюга мм	Вантажопідйомність тон	Ефективна робоча довжина m	WLL 0-45° t	WLL 45-60° t
241301300800310	13	14	8	14	10
241301600200310	16	21,2	2	21,2	15
241301600300310	16	21,2	3	21,2	15
241301600400310	16	21,2	4	21,2	15
241301600500310	16	21,2	5	21,2	15
241301600600310	16	21,2	6	21,2	15
241301600700310	16	21,2	7	21,2	15
241301600800310	16	21,2	8	21,2	15